



VOLTA平面皮帶技術資料

註：■有 △只有FDA



特性 型號	厚度 THICK- NESS mm	硬度 HARD- NESS SHORE A	最小輪徑 MINIMUM PULLEY DIAMETER mm	重量 WEIGHT kg/m ²	槽型輸送 TROUGHED	摩擦係數 COEFFICIENT OF FRICTION		抗拉 強度 K1%PER WIDTH Kg/Cm	防靜電 處理 ANTISTATIC 1x10 ⁹ Ω	食品 檢驗 FOOD APP. FDA/USDA
						TOP	BOTTOM			
FEZ-2	2	95	30	2.5	■	0.4	0.2	1.2		
FEZ-3.2	3.2	95	48	4.0	■	0.4	0.2	2.0		
FEZ-4	4	95	60	5.0	■	0.4	0.2	2.6		
FK-1.8	1.8	100	60	2.3		0.3	0.3	1.9		
FK-4	4	100	105	5.0		0.3	0.3	4.2		
FEMW-2	2	95	28	2.5	■	0.4	0.2	1.2		■
FEMW-3	3	95	40	3.8	■	0.4	0.2	1.8		■
FMW-4	4	95	60	5.0	■	0.4	0.4	2.4		■
FHW-2	2	100	70	2.5	■	0.3	0.3	2.0		■
FRGZ-2	2	95	27/50	2.5	■	0.4	0.2	6.0	■	
FRGZ-3	3	95	36/70	3.8	■	0.4	0.2	7.0	■	
FRG-2	2	95	27/50	2.5	■	0.4	0.2	6.0	■	
FRMW-2.3	2.3	95	27/50	2.5	■	0.4	0.2	6.0	■	△
FRL-3	3	80	30/60	3.6	■	0.8	0.2	12.0	■	△
FRL-5	5	80	60/120	6.0	■	0.8	0.2	13.0	■	△
FELW-2	2	80	10	2.5	■	0.8	0.3	1.0		■
FRLW-2	2	80	10/25	2.5	■	0.8	0.2	6.0	■	△
FHB-3	3	100	90	3.8		0.3	0.3	3		■